

SLST3-6

Industrial extended stainless steel PT1000 temperature sensor

User Manual

File Version: V19.8.27



SLST3-6The kernel is imported from Germany. PT1000 is a platinum thermal resistance,and its resistance will change with temperature. The 1000 after the PT character means that it has a resistance of 1000 ohms at 0 °C,at 300 °C. Its resistance is about 2120.515 ohms. Its working principle: When the PT1000 is at 0 degrees Celsius,its resistance is 1000 ohms,its resistance will increase with temperature and its resistance will increase at a constant rate. SLST3 -20PT1000 sensor platinum resistance is made of platinum wire with purity of 99.9995%. It has stable performance,good repeatability,high precision and good linearity in a certain temperature range. It is an internationally recognized mature product,international temperature standard ITS-90. It is also stipulated that the platinum resistance with special structure is used as the standard thermometer of 13.5033K--961.78 °C. The platinum resistance is widely used for the temperature in the range of -200--850 °CMeasurement,industry is usually below 600 ° C,the temperature range of different models of SLST3 see technical parameters. Very low power consumption,making SLST3-X the first choice for various applications.

Technical Parameters

Technical parameter	Parameter value
Brand	SONBEST
Temperature measurement range	-50°C to +100°C (optional with other ranges)
Detecting Core Devices	PT1000
Temperature Measurement Accuracy	± 0.3°C (optional ±0.3°C)
Thermal Response Coefficient	10mΩ/K
The resistance of the sensor at 0 °C	1000Ω±0.12Ω/K
The resistance of the sensor at 0-100 °C	3.85Ω/K
Reference Execution Standards	Using EN 60751 Class B Standards
Communication Interface	1-WIRE BUS
Power	DC3~5.5V

Contact Us

Company: Shanghai Sonbest Industrial Co., Ltd

Address:Building 8,No.215 North east road,Baoshan District,Shanghai,China

Web: <http://www.sonbest.com> <http://www.sonbus.com>

SKYPE: soobuu

Email: sale@sonbest.com