

# **SLST3-2**

# Mounted stainless steel package PT1000 temperature sensor User Manual

File Version: V19.8.27





SLST3-2The kernel is imported from Germany. PT1000 is a platinum thermal resistance, and its resistance will change with temperature. The 1000 after the PT character means that it has a resistance of 1000 ohms at 0 °C, at 300 °C. Its resistance is about 2120.515 ohms. Its working principle: When the PT1000 is at 0 degrees Celsius, its resistance is 1000 ohms, its resistance will increase with temperature and its resistance will increase at a constant rate. SLST3 -20PT1000 sensor platinum resistance is made of platinum wire with purity of 99.9995%. It has stable performance, good repeatability, high precision and good linearity in a certain temperature range. It is an internationally recognized mature product, international temperature standard ITS-90. It is also stipulated that the platinum resistance with special structure is used as the standard thermometer of 13.5033K--961.78 °C. The platinum resistance is widely used for the temperature in the range of -200--850 °CMeasurement, industry is usually below 600 °C, the temperature range of different models of SLST3 see technical parameters. Very low power consumption, making SLST3-X the first choice for various applications.

### **Technical Parameters**

Technical parameter	Parameter value	
Brand	SONBEST	
Temperature measurement range	-50°C to +100°C (optional with other	
	ranges)	
Detecting Core Devices	PT1000	
Temperature Measurement Accuracy	± 0.3°C (optional ±0.3°C	
Thermal Response Coefficient	10mΩ/K	
The resistance of the sensor at 0 °C	1000Ω±0.12Ω/K	
The resistance of the sensor at 0-100 °C	3.85Ω/K	
Reference Execution Standards	Using EN 60751 Class B Standards	
Power	DC3~5.5V	

## Wiring instructions

Any incorrect wiring can cause irreversible damage to the product. Please carefully wire the cable as follows in the case of power failure, and then connect the cable to confirm the correctness and then use it again. Some products have no lead, the core color is for reference only.

ID	Core color	Identification	Note
1	Red BLACK	R-	One foot of the
			resistor
2	Blue	R+	Another foot of the
			resistor

### **Contact Us**

Company: Shanghai Sonbest Industrial Co., Ltd

Address: Building 8, No. 215 North east road, Baoshan District, Shanghai, China

Web: http://www.sonbest.com http://www.sonbus.com



SKYPE: soobuu

Email: sale@sonbest.com